

SITE LIGHTING FIXTURE SCHEDULE


SYMBOL	TYPE	MANUFACTURER CATALOG	LAMP TYPE	BALLAST	FIXTURE WATTAGE	VOLTS	REMARKS
	SA	VISIONAIRE LIGHTING #ODN-2-L-**-80LC-7-3K-UNV-AML-BK-C5/H1-CLS	LED 4000K 10000L MIN.	0-10V DIMMING	177	120	LED POST TOP FIXTURE. 12'-0" A.F.F TO BOTTOM OF FIXTURE ON 4" SQUARE NON-TAPERED 11 GAUGE BLACK STEEL POLE ON 30" RAISED FOOTING. SINGLE BOLT-ON ARM ** DISTRIBUTION AS INDICATED ON PLANS
	SB	VISIONAIRE LIGHTING #SNTS-4S-11-14'-98C-343-D2-BK	LED 3000K 1200L MIN.	0-10V DIMMING	22	120	4" A.F.F. LED BOLLARD WITH ASYMMETRICAL DISTRIBUTION. ** FINISH PER ARCHITECT ** DISTRIBUTION AS INDICATED ON PLANS
	SC	ALED LIGHTING #LLS-4-VHE-41-B-40	LED 4000K 5000L MIN.	-	41	120	4' LED STRIP LIGHT. FOR CARPORTS
	SD	EVERGREEN LIGHTING #EVOL-W-27-2715LED-ABR-WDA	LED - 2000L MIN.	-	15	120	27" DECORATIVE EXTERIOR LED WALL SCONCE. FLAT BAR FIN DESIGN. ETL RATED FOR WET LOCATION
	SE	BK LIGHTING #PTR-6-**-AR-LED-TR-x53-SP-**-12-11-B-010-MT	(6) 10W 1230 LUMEN LED, 3000K	0-10V DIMMING	60	120	LED TREE RING LIGHT. * STRAP SIZE TO BE DETERMINED BEFORE ORDERING.PROVIDE TRANS/DRIVER SIZE AS REQUIRED. FIXTURE SHALL BE 3 UP 3 DOWN. ** ARCHITECT TO DETERMINE FINISH.
	SF	TIVOLI #LSL-B-CS-H-27-C-12 #SHADE-HT-BK-BK-B	LED 150L/FT. MIN.	0-10V DIMMING	1.8W/FT.	120	LED FESTOON LIGHTING WITH 24" SPACING WITH HAT SHADE.
	SG	TRACE LITE #E110-27-VS-3K-BR-PC	LED 3000K 700L MIN.	0-10V DIMMING	27	120	LED WALL SCONCE DOWNLIGHT. WITH PHOTOCONTROL BUTTON
	SH	JUNO LIGHTING #JSF-5IN-07LM-30K-90CRI-MVOLT	LED 3500K 1900L MIN.	0-10V DIMMING	16	120	4' LED FIXTURE FOR USE AT MONUMENT SIGN. FIXTURE TO BE MOUNTED MINIMUM 4" ABOVE FINISHED GRADE PER MANUFACTURER. * INDICATES FINISH PER ARCHITECT
	SV	ORGATECH LIGHTING #1400S-4-LS-35-AC120-45-SW-**-P-G	LED 3500K 1900L MIN.	0-10V DIMMING	16	120	4' LED FIXTURE FOR USE AT MONUMENT SIGN. FIXTURE TO BE MOUNTED MINIMUM 4" ABOVE FINISHED GRADE PER MANUFACTURER. * INDICATES FINISH PER ARCHITECT
	SK	BK LIGHTING #PTR-4-**-DE-LED-TR-x59-MFL-**-12-11-B-INC-MT	(4) 12W 1500 LUMEN LED, 3000K	0-10V DIMMING	48	120	LED TREE RING LIGHT. * STRAP SIZE TO BE DETERMINED BEFORE ORDERING.PROVIDE TRANS/DRIVER SIZE AS REQUIRED. FIXTURE SHALL BE 2 UP 2 DOWN. ** ARCHITECT TO DETERMINE FINISH.

SITE PHOTOMETRICS STATISTICS SUMMARY


Statistics						
Description	Symbol	Avg	Max	Min	Max/Min	Avg/Min
0' from preserve line	+	0.0 fc	0.0 fc	0.0 fc	N/A	N/A
50' from preserve line	+	0.1 fc	0.2 fc	0.0 fc	N/A	N/A
100' from preserve line	+	2.7 fc	12.5 fc	0.0 fc	N/A	N/A
automotive hardscape	+	2.0 fc	18.0 fc	0.2 fc	90.0:1	10.0:1
Courtyard	+	2.8 fc	4.2 fc	1.6 fc	2.6:1	1.8:1
East Pedestrian Hardscape Bld 10 Center	+	2.1 fc	9.9 fc	0.4 fc	24.8:1	5.3:1
East Pedestrian Hardscape Bldg 10	+	1.8 fc	5.2 fc	0.5 fc	10.4:1	3.6:1
East Pedestrian Hardscape Bldg 11	+	4.7 fc	18.1 fc	0.4 fc	45.3:1	11.8:1
East Pedestrian Harscape Bldg 8	+	2.5 fc	14.9 fc	0.4 fc	37.3:1	6.3:1
East preserve pedestrian hardscape	+	3.3 fc	14.9 fc	0.4 fc	37.3:1	8.3:1
Pool Boundary	+	1.8 fc	5.2 fc	1.0 fc	5.2:1	1.8:1
Pool Enclosure	+	4.5 fc	26.8 fc	1.1 fc	24.4:1	4.1:1
Pool Jacuzzi Boundary	+	2.9 fc	4.8 fc	2.2 fc	2.2:1	1.3:1
West Pedestrian Hardscape Bldg 1.2	+	4.3 fc	13.5 fc	0.5 fc	27.0:1	8.6:1
West Pedestrian Hardscape bldg 3	+	3.4 fc	14.5 fc	0.3 fc	48.3:1	11.3:1
West Pedestrian Hardscape Bldg 5.4	+	3.3 fc	14.2 fc	0.5 fc	28.4:1	6.6:1
West Pedestrian Hardscape Building 1	+	1.6 fc	3.9 fc	0.3 fc	13.0:1	5.3:1
West Pedestrian Hardscape Center	+	2.7 fc	16.3 fc	0.3 fc	54.3:1	9.0:1
West Pedestrian hardscape	+	5.0 fc	34.9 fc	0.2 fc	174.5:1	25.0:1
Dog Park	+	1.1 fc	3.5 fc	0.2 fc	17.5:1	5.5:1

SITE LIGHTING SHEET INDEX

E-0.0	SITE LIGHTING COVER SHEET
E-0.1	SITE LIGHTING FIXTURE CUTSHEETS
E-0.2	SITE LIGHTING FIXTURE CUTSHEETS
E-0.3	SITE LIGHTING FIXTURE CUTSHEETS
E-1.0	SITE LIGHTING LAYOUT
E-1.1	SITE LIGHTING PHOTOMETRICS



Consultant



#2022-02027


Client

HOMEFED CORPORATION
1903 WRIGHT PLACE, SUITE 220
CARLSBAD, CA 92008
TEL. (760) 918-8200

ESCAYA II
APARTMENTS
XXXX
CHULA VISTA, CA XXXX

SITE LIGHTING COVER SHEET

CD 04/27/2022
Project Number: 2021-084
Plan Check Number: #



S H E E T

E0.0

TYPE TYPE TYPE TYPE 

Juno

Project:
Fixture Type:
Location:
Contact/Phone:

JUNO SLIMFORM™ LED
SURFACE MOUNT DOWNLIGHTS
FOR JBOX INSTALLATION
5", 7", 11", 13" ROUND
JSF SERIES

PRODUCT DESCRIPTION

Steel, ultra-low profile energy efficient LED surface mount downlights in multiple sizes from 5" to 13" • Provides economical installation by mounting directly over standard and fire-rated junction boxes • Optional finish trim available for custom, designer look similar to standard recessed downlights • Provides general illumination in residential and commercial applications including multifamily and hospitality • Ideal for use in corridors, living spaces, closets, hallways, pantries, stairways, outdoor covered areas with Emergency Option and much more.

PRODUCT SPECIFICATIONS

Construction Shallow, less than 1", solid ring with white finish • Non-conductive fixture for shower/light applications • Optional, field installable finish trim available for 5" and 7" versions to change the exterior finish of fixture

Optics Light guide technology combined with diffusing lens conceals the LEDs from direct view and provides uniform lens luminance • LED Light Engine: LEDs mounted directly to heatlink designed to provide superior thermal management and ensure long life • 2700K, 3000K, 3500K or 4000K LED color temperature • LEDs binned for 4-step MacAdam ellipse color consistency • 90 CRI minimum

LED Driver Choice of dedicated 120 volt (120 Watt) or universal voltage (MVOLT) driver that accommodates input voltages from 120-277 volts AC at 50/60Hz • Power factor > 0.9 at 120V input • 120 volt driver is dimmable with the use of most incandescent, magnetic low voltage and electronic low voltage wall box dimmers • Universal voltage driver is dimmable with the use of most 0-10V wall box dimmers • External driver is only available on 5" and 7" models • For a list of compatible dimmers, see [JUNOSPECIFICATIONS](#)

Emergency Battery Option Available on fixture sizes 11" and larger • Battery factory assembled to fixture with integral test switch • Drives LEDs for 90 minutes to meet Life Safety Code (NFPA54), National Electrical Code (NEC), and UL requirements • Title 20 certified battery pack available when ordering E110XCT option • ERS option provides back box without battery for constant look when used in some spaces as fixtures with ELS emergency option • Dump location only with emergency option

Life Rated for 50,000 hours at 70% lumen maintenance

Labels ENERGY STAR® certified • Certified to the high efficacy requirements of California Title 24 (2016) • CSA Listed for US and Canada • Suitable for wet locations (covered ceilings) • Dump location only with emergency option

Testing All reports are based on published industry procedures; actual performance may differ as a result of the end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C.

Warranty 5-year limited warranty. This is the only warranty provided and no other statements in this specification sheet create any warranty of any kind. All other express and implied warranties are disclaimed. Complete warranty terms located at: [www.acuitybrands.com/support/centralusa/terms-and-conditions](#)

Notes: Actual performance may differ as a result of end-user environment and application. All values are design or typical values, measured under laboratory conditions at 25 °C. Specifications subject to change without notice.

One Mission Way • Canyon, CA 92012 • Phone 1-800-705-SERV (7378) • Visit us at [www.acuitybrands.com/junorecessed](#)
Printed in U.S.A. © 2017/2022 Acuity Brands Lighting, Inc. Rev. 02/09/22

1 of 3

TRACE•LITE
commercial & industrial lightingE110X Series
Architectural LED Trapezoid Wallpack

DESCRIPTION
The E110X Series is a traditional full cutoff geometric sconce designed for optimal light control and distribution. Its die-cast aluminum construction provides ideal thermal management. Lumen packages from 3500 to 12,200 are available in 3000K, 4000K and 5000K CCT with a Type III distribution. This product offers project flexibility with photocell, integral motion sensor and battery backup options. The E110X is PREMIUM DLC-C Qualified for maximum energy savings and utility rebates. This architectural family is offered in two housing sizes to complement new construction or retrofit applications, accommodating mounting heights up to 30'.

SPECIFICATIONS
Construction:
• Die-cast aluminum housing in a powder coated bronze finish with stainless steel hardware
• UV-stabilized polycarbonate lens
• Integral heat sink maximizes heat dissipation for longer LED life
• Tinged back box isolates drivers from LEDs and offers easy access to drivers
• Back box includes three conduit entry points (one on top and two on the sides) as well as a knockout on the bottom for optional sensor

Optical/LEDs:
• No uplight design to minimize light pollution
• 27W to 36W LED models replace 100W to 400W HID for up to 70% energy savings
• Efficacies up to 135 LPW maximize utility rebates
• Type III distribution
• Available in 3000K, 4000K and 5000K CCT
• CRI > 90
• 70,000 hours L70

Electrical:
• 120-277VAC, 50/60Hz
• 1-10V Dimming driver
• 3000K, 4000K, 5000K
• 370
• Input Voltage: 120-277VAC, 50/60Hz
• Operating Temp: -40°C to 40°C (-40°F to 113°F)
• Certifications: cULus Listed for Wet Locations, DLC PREMIUM for specific models
• Operating temperatures: -40°C to 40°C (-40°F to 113°F)

Testing & Compliance:
• cULus Listed for Wet Locations
• DesignLights Consortium® (DLC) PREMIUM Qualified (consult CPL for specific models)
• Operating temperatures: -40°C to 40°C (-40°F to 113°F)

Installation:
• Housing tingers to back box for easy installation
• Back box accommodates conduit entry as well as optional sensor
• Mounts to a standard 3-1/2" or 4" square electrical J-box





















Options:
• Integral battery backup (BB) operates for 90 minutes, providing over 800 lumens for path of egress. Rated for ambient temperatures of 0°C to 40°C (32°F to 104°F)
• Factory installed integral dimming occupancy sensor (SC)

Accessories:
• Dimming sensor for field installation (TL-MSSW)
• Remote control for TL-MSSW sensor (TL-MSSW-REMOTE)
• Button type universal photocell sensor (120/277VAC: PCU)

Warranty:
• Five Year Warranty (Terms and Conditions Apply)

Specifications are subject to change without notice. Installation must be performed in accordance with Barron Lighting Group installation instructions.

100-10386 Rev. 4



tiroli

PHOTOMETRY | Litesphere

Standard Spacing Options & Max Run Chart


	6" OC	12" OC	18" OC	24" OC
STANDARD (H)	11	29.9	180	6
HIGH (V)	6	15	90.2	4
VERY HIGH (V)	4	10	60	3
Lumens Per Foot	.11	.46	1.92	.09
Watts Per Foot	.17	.46	1.92	.09
*Max Single Run	100'	60'	30'	150'

Lumens Per Watt STD 40 HO 46 VHO 94

Tested @ 3000K w/ clear globe

*Max run lengths based on Tivoli's recommended lumen drops.

Lowest operating temperature for systems: -40°F



Tivoli LLC reserves the right to modify this specification without prior notice.

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

ARTISTAR - PALM TREE RING LED (INTEGRAL)

IP66 RATED

DATE: _____ PROJECT: _____ TYPE: _____
CATALOG NUMBER LOGIC: _____

CATALOG NUMBER LOGIC:

E-Series: PTR - 4 - 26 - AR - LED - TR - x53 - SP - 62W - 12 - 11 - B - INC - MT

MATERIAL: Aluminum

SERIES: PTR - Palm Tree Ring

FIXTURE QUANTITY: 2 - 2 @ 180° 4 - 4 @ 90°

3 - 3 @ 120° 6 - 6 @ 60°

STRAP SIZES: 16 - 16" min. to 22" max. tree diameter

21 - 21" min. to 27" max. tree diameter

26 - 26" min. to 32" max. tree diameter

31 - 31" min. to 38" max. tree diameter

FIXTURE: AR - ArchStar

SOURCE: LED - Chip on Board Technology

HOUSING: TR - Integral Transformer

LED TYPE: x53 - 10W LED/2700K x53 - 10W LED/3000K x54 - 10W LED/4000K

OPTICS: SP - Spot (20°) FL - Flood (40°) MFL - Medium Flood (60°)

FINISH (See page 2 for full-color swatches): Standard Finishes (B2P, B2W, BLU, BLW, WHR, WHW, SAP, VER)

Premium Finish (ABP, AMG, AQW, BCM, BGE, BPP, CAP, CMG, CRI, CRM, HUG, MOS, NBP, OCP, RAG, SCS, SMC, TVE, WCP, WVR)

Also available in RAL Finishes

LENS TYPE: 12 - Soft Focus 13 - Rectilinear

SHIELDING: 11 - Honeycomb Baffle (per fixture)

CAP STYLE: A - 45° (per fixture)

B - 90° (per fixture)

C - Flush

F - 90° Cutoff with Flush Lens (per fixture)

CONTROL TYPE: 010 - 0-10 Dimming

INC - Dimming Driver (For use with Incandescent dimmer)*

INPUT VOLTAGE: MT - 120-277 VAC Input

THE DOCUMENT CONTAINS PROPRIETARY INFORMATION OF B-K LIGHTING, INC. AND IS NOT TO BE REPRODUCED OR USED WITHOUT SPECIFIC WRITTEN AUTHORIZATION OF B-K LIGHTING, INC. IS STRICTLY FORBIDDEN.

12/14/2021 BKL - 1259

508-2810-00

B-K LIGHTING MADE IN THE USA 859.438.5800 INFO@BKLIGHTING.COM BKLIGHTING.COM

100-10386 Rev. 4

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20


Page 5 of 11

[www.tivolilighting.com](#) tel: 714-957-6101 fax: 714-427-3458

Copyright © Tivoli 12/04/20

Page 5 of 11

SHEET



Consultant



SALASOBRIEN

1103 TIMBER CANYON ROAD

SUITE 201

CORNWALL, CA 92033

TEL: (949) 753-1553

06-09-22

www.salasobrien.com

E-Mail: mail@salasobrien.com

#2022-02027

Client

HOMERED CORPORATION

1903 WRIGHT PLACE, SUITE 220

CARLSBAD, CA 92008

TEL: (760) 918-8200

XXXX

CHULA VISTA, CA XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

XXXX

TYPE SK

DENALI - PALM TREE RING LED (INTEGRAL)IP66 RATED

DATE:PROJECT:TYPE:

CATALOG NUMBER LOGIC:



*Accommodates up to 2 lens/shielding/cap media.
Price reflects per fixture cost.

CATALOG NUMBER LOGIC

MATERIAL

SERIES

FIXTURE QUANTITY

STAP SIZES

FIXTURE

SOURCE

HOUSING

LED TYPE

OPTICS

FINISH

LENS TYPE

SHIELDING

CAP STYLE

CONTROL

INPUT VOLTAGE

B-K LIGHTINGMADE IN THE USA559.438.5880 | INFO@BKLIGHTING.COM | BKLIGHTING.COM

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF B-K LIGHTING, INC. AND ITS RECEIPT OR POSSESSION DOES NOT CONVEY ANY RIGHTS TO REPRODUCE, DISCLOSE ITS CONTENTS, OR TO MANUFACTURE, USE OR SELL, ANYTHING IT MAY DESCRIBE. REPRODUCTION, DISCLOSURE OR USE WITHOUT SPECIFIC WRITTEN AUTHORIZATION OF B-K LIGHTING, INC. IS STRICTLY FORBIDDEN.

TYPE SU

ORGATECH

Architura Signlighter 1400S


Flood or Wallwash LED

120V or 277VAC

Project

Type

Date



Driverless 120V or 277V LED Arrays with 45° or 120° distribution for general signlighting and wallwashing creates a powerful energy efficient and economical linear floodlight for replacement of fluorescent luminaries with formed reflectors to create flood and asymmetric outputs. Adjustable aiming. Field replaceable LED modules. Color temperature, driver, voltage, optics, mounting options and finish are all selectable to customize the fixture to your specific application.

Construction Powder coated aluminum with cast endcaps. Removable polycarbonate lenses enable LEDs to be replaced for future maintenance.

Mounting Swivels, Extended arms, L bracket or Permapost.

Electrical 120VAC or 277VAC. Individually powered by back exiting 24" long 18/3 weatherproof cord, with a liquid tight connector for connection to a J-Box. Reverse phase dimmable (ELV).

Finish Powder coated silver, black, bronze or white. Marine Grade option available.

Warranty 5yr/50,000 hour limited warranty.

Environment Wet Location - IP65. Operating Temperature -22°F to 122°F.

Certifications UL Listed 1598.

LS - 4 Watts/Ft.	480 Lm/Ft
Optics	45°, 120°
Length (Nom.)	2ft 3ft 4ft 8ft
Wattage	8W 12W 16W 32W
Lumens	960 1,440 1,920 3,840
CRI	90

LH - 8 Watts/Ft.	960 Lm/Ft
Optics	120°
Length (Nom.)	2ft 3ft 4ft 8ft
Wattage	16W 24W 32W 64W
Lumens	1,920 2,880 3,840 7,680
CRI	90

Photometric Comparison - Typical Fc @10'

Lens	120°	45°
FC @10' (4W)	8fc	22fc
FC @10' (8W)	16fc	NA


Series	Length	LED Output	CCT	Voltage	Optics	Mounting	Finish	Options
1400S	2 2' Nom.	LS Standard	27 27K	AC120 120V	45 45°	SW Swivel Mount	SO Silver	P Permapost
	3 3' Nom.	LH High	30 30K	AC277 277V	45 45° not available for LH	SB Sliding Bracket	BL Black	G Glare Shield
	4 4' Nom.		35 35K			WH White	BZ Bronze	Ax Extended Arm
	8 8' Nom.		40 40K			CU Custom	WH White	N None
			50 50K			Bracket	RAL	
						Hub	x=4"-36" length	
							length	

Specifications are correct at the time of publishing, but may be modified or improved without notification. 8/20

Orgatech | 205 W. Blueridge Avenue, Orange, CA 92865 | 626.969.6820 | www.orgatech.com

DENALI - PALM TREE RING LED (INTEGRAL)IP66 RATED

DATE:PROJECT:TYPE:



*Accommodates up to 2 lens/shielding/cap media.
Price reflects per fixture cost.

CATALOG NUMBER LOGIC

MATERIAL

SERIES

FIXTURE QUANTITY

STAP SIZES

FIXTURE

SOURCE

HOUSING

LED TYPE

OPTICS

FINISH

LENS TYPE

SHIELDING

CAP STYLE

CONTROL

INPUT VOLTAGE

B-K LIGHTINGMADE IN THE USA559.438.5880 | INFO@BKLIGHTING.COM | BKLIGHTING.COM

THIS DOCUMENT CONTAINS PROPRIETARY INFORMATION OF B-K LIGHTING, INC. AND ITS RECEIPT OR POSSESSION DOES NOT CONVEY ANY RIGHTS TO REPRODUCE, DISCLOSE ITS CONTENTS, OR TO MANUFACTURE, USE OR SELL, ANYTHING IT MAY DESCRIBE. REPRODUCTION, DISCLOSURE OR USE WITHOUT SPECIFIC WRITTEN AUTHORIZATION OF B-K LIGHTING, INC. IS STRICTLY FORBIDDEN.

ORGATECH

Architura Signlighter 1400S

Lensing & Photometrics

Energy efficient lens selection and application matching: for optimal energy efficiency and reliability.

Photometric Data - LS 4W/ft

Photometric Data - LH 8W/ft

Mounting Options

SW - Swivel Mount

P - Permapost

G - Glare Shield

SB - Sliding Bracket

Specifications are correct at the time of publishing, but may be modified or improved without notification. 8/20

Orgatech | 205 W. Blueridge Avenue, Orange, CA 92865 | 626.969.6820 | www.orgatech.com

Consultant

#2022-02027

Client

HOMEFED CORPORATION
1903 WRIGHT PLACE, SUITE 220
CARLSBAD, CA 92008
TEL: (760) 918-8200


ESCAPA II
APARTMENTS
XXXX
CHULA VISTA, CA XXXX

SITE LIGHTING FIXTURE CUTSHEETS

CD 04/27/2022
Project Number: 2021-084
Plan Check Number: #

E0.3

SHEET



SALAS O'BRIEN
[expect a difference]

4160 TEMESCAL CANYON ROAD
SUITE 201
CORONA, CA 92883
TEL: (949) 753-1553

06-09-22
www.salasobrien.com
E-Mail: mail@ombengrs.com

Client


HOMEFED CORPORATION
1903 WRIGHT PLACE, SUITE 220
CARLSBAD, CA 92008
TEL. (760) 918-8200

ESCAPA II
APARTMENTS
XXXXX
CHULA VISTA, CA XXXXX

SITE LIGHTING PHOTOMETRICS

CD 04/27/2022

Project Number:	2021-084
Plan Check Number:	#



S H E E T

E-1.1